

PROFESSIONAL

WOOD - PRODUCT DATASHEET 2021



TECHNICAL DATA (EN 13489)		13 mm	14 mm	22 mm
Reaction to fire	EN 14342 Table 1 (when applicable) / EN 13501	Dfl-s1		
Emission of formaldehyde	EN 14342	E1		
Brinell hardness (average value) Oak	(BHN) EN1534	3,7		
Taber Abraser/Lacquer's wear resistance Protoco Lacquer Protoco Natura <i>These typical values are not applicable for stained, brushed or hardwax oiled products.</i>	EN 13696	4000 3500		
Reduction of sound weighted index ΔL_w in dB with 2 mm Tarkofoam/flex II	EN ISO 10140-3 / EN ISO 717-2	≥ 17		
Thermal insulation value (RT m ² K/W) board only with rag felt with 2 mm Tarkofoam/flex II	EN ISO 10456:2007	0,101 0,121 0,141	0,152 0,182 0,192	
Thermal conductivity (W/m K)	EN 12664 / EN 14342:2013	0,104	0,11	0,136
Construction	3-layer with softwood core			

INSTALLATION	
Installation method	10-14 mm: Floating or glue down 22 mm: Nailed or glue down Floating max area 30 m ²
Installation instruction	Download from www.tarkett.com Contact your supplier for more details
Underfloor heating compatible Maximum floor surface temperature 27°C with self-regulating under-floor heat system	Yes
Start & Stop: Shorter lengths of planks included in approx. 1 pack per 20 m ²	

RECOMMENDED ACCESSORIES	
Installation	Tarkofoam II / Tarkoflex II Installation kit
Aesthetics	Skirting, Transition moulding, Pipe covers
Care & Maintenance	Wood Floor Care Kit / Spray Mop Kit Bioclean Refresher
See more alternatives and the complete range of accessories @ www.tarkett.com	

MAINTENANCE
These Tarkett wooden floors have a Protoco surface treatment and therefore a strong protection against normal wear, abrasion, scratches and stains. Some floors will require more frequent maintenance for increased life span. Generally these products are light coloured floors and hardwax oiled floors, particularly with brushed surface and/or highlighted details, such as saw marks. Please always refer to maintenance guidance available on websites.
See maintenance instructions @ www.tarkett.com



2-LOCK



T&G



Protoco



www.realwood.eu

PROFESSIONAL

WOOD - PRODUCT DATASHEET 2021

DESIGN

Real wooden floors for special applications.


PRODUCT DATA	Material code	Dimensions LxWxH (mm)	Pattern	Surface treatment	Surface effect	Bevel (4 side)	Character	Colour	Latin name	DoP no.	Wear layer thk (mm)	Board/ pack	m ² / pack	m ² / pallet	Net weight/ m ² (kg)
PROFESSIONAL 13 MM															
Oak Nature	8722011	2 027 x 194 x 13	3-strip	Proteco Lacquer	-	-	Calm	Warm brown	2	0020-0104	2,5	6	2,36	94,40	7,3
	8722002	2 027 x 194 x 13	3-strip	Proteco Natura	-	-	Calm	Warm brown	2	0020-0104	2,5	6	2,36	94,40	7,3
PROFESSIONAL 14 MM															
Oak Nature	8721001	2 027 x 194 x 14	3-strip	Proteco Lacquer	-	-	Calm	Warm brown	2	0020-0106	3,5	6	2,36	94,40	7,9
	8721002	2 027 x 194 x 14	3-strip	Proteco Natura	-	-	Calm	Warm brown	2	0020-0106	3,5	6	2,36	94,40	7,9
PROFESSIONAL 22 MM															
Ash Contrast White	7951007	2 535 x 194 x 22	3-strip	Proteco Natura	-	-	Lively	Warm beige	1	0020-0117	3,5	4	1,97	68,95	10,6
Oak Robust White	7825901	2 535 x 194 x 22	3-strip	Proteco Natura	-	-	Lively	Warm beige	2	0020-0117	3,5	4	1,97	68,95	10,6
Ash Nature	7949009	2 535 x 194 x 22	3-strip	Proteco Natura	-	-	Calm	Warm beige	1	0020-0117	3,5	4	1,97	68,95	10,6
Ash Contrast	7950007	2 535 x 194 x 22	3-strip	Proteco Natura	-	-	Lively	Warm beige	1	0020-0117	3,5	4	1,97	68,95	10,6
Beech Contrast	7911005	2 535 x 194 x 22	3-strip	Proteco Lacquer	-	-	Lively	Warm beige	3	0020-0117	3,5	4	1,97	68,95	10,6
Oak Nature	7825011	2 535 x 194 x 22	3-strip	Proteco Lacquer	-	-	Calm	Warm brown	2	0020-0117	3,5	4	1,97	68,95	10,6
	7825010	2 535 x 194 x 22	3-strip	Proteco Natura	-	-	Calm	Warm brown	2	0020-0117	3,5	4	1,97	68,95	10,6

Due to the nature of the material this table shows typical values.

1: Fraxinus Angustifolia, 2: Quercus Robur & Quercus Petraea, 3: Fagus Sylvatica,



Oak Nature



Ash Contrast White



Oak Robust White



Ash Nature



Ash Contrast



Beech Contrast

The pictures only present the colour of the floor. For more details regarding grading and variations see the Grading Book or www.tarkett.com. Tarkett's international range of floors comprises many different products. Some of these may not be for sale in your country. Although every care has been taken to reproduce images that reflect the finished product, the quality of monitor and printer and the nature of wood results in variations in the color and structure of individual planks. When sanding a wooden floor the appearance will change in colour, texture and surface effects.

For further and latest information please visit www.tarkett.com