

# TECHNICAL DATA iD Inspiration Click & Click<sup>PLUS</sup>

Certification & classification	Standards	Inspiration Click <sup>PLUS</sup>
Type of floor covering	EN ISO 10582	Heterogeneous Compact Resilient Floorcovering
CE certification	EN 14041	Yes
Classification	EN ISO 10874	Domestic: 23 Commercial: 33 Industrial: 42
<b>Technical characteristics</b>		
Total thickness	EN ISO 24346	4.5 mm
Wear layer thickness	EN ISO 24340	0.55
Surface treatment (PUR)		Yes - TopCleanXP™
Total weight	EN ISO 23997	8000 g/m <sup>2</sup>
Beveled edges		Yes
Wear layer binder content	EN ISO 10582	Type I
Dimensions	EN ISO 24342	
	Planks	19.05 x 121.10 cm - 7 planks/box = 1.66 m <sup>2</sup> 24.05 x 149.10 cm - 5 planks/box = 1.79 m <sup>2</sup>
	Tiles	49.05 x 99.10 cm - 3 tiles/box = 1.46 m <sup>2</sup>
<b>Technical performances</b>		
Dimensional stability	EN ISO 23999	≤ 0,10 %
Curl resultant to heat	EN ISO 23999	≤ 2 mm
Reaction to fire	EN 13501-1	B <sub>n</sub> -s1
Residual indentation	EN ISO 24343-1	≤ 0 10 mm
Furniture leg	EN 424	No damage
Castor chair	ISO 4918 - EN 425	No damage
Impact sound reduction	EN ISO 717-2	ΔL <sub>w</sub> = 3 dB
Reduction of in-room impact noise	EN ISO 31-074	Class C (L <sub>n,ew</sub> < 85 dB)
Thermal resistance	EN ISO 10456	0 04 m <sup>2</sup> K/W
Light fastness	EN ISO 105-B02 (method 3a)	≥ 6
Chemical resistance	EN ISO 26987	Very good
Slip resistance	DIN 51130 EN 13893	R9 / R10 depending on embossing μ ≥ 0 30
Electrical properties	EN 1815 EN 1081	< 2 kV on concrete ≥ 10 <sup>9</sup> Ohm
Underfloor heating		Suitable - max. 27 °C
Adhesion wear layer	EN ISO 24345	≥ 50N / 50mm
Colours		22

The above information is subject to modification for the benefit of further improvement. (10/17).

Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for these instructions.



According to Classification ISO 10874

