

iD REVOLUTION

TECHNICAL DATA

Certification & classification	Standards	iD Revolution	
Type of floor covering	EN 14565 - ISO 19322	Resilient floor covering based upon synthetic thermoplastic polymers	
Classification	EN ISO 10874	Domestic: 23 Commercial: 33 Industrial: 42	
Technical characteristics			
Total thickness	EN ISO 24346	2.5 mm	
Wear layer thickness	EN ISO 24340	0.55 mm	
Total weight	EN ISO 23997	3900 g/m ²	
Form of delivery	EN ISO 24342	Planks	12.5 x 122 cm, 24 planks/box = 3.66 m ² 20 x 122 cm, 15 planks/box = 3.66 m ² 25 x 122 cm, 12 planks/box = 3.66 m ²
		Tiles	25 x 50 cm, 30 tiles/box = 3.75 m ² 50 x 50 cm, 15 tiles/box = 3.75 m ² 50 x 100 cm, 7 tiles/box = 3.50 m ²
Surface treatment (PUR)		Yes - TopClean XP™	
Beveled edges		Yes	
CE Marking			
Declaration of Performance		0007-0049-DoP-2018-06	
Technical performances			
Dimensional stability	ISO 19322 - PROCEDURE A	≤ 0.15%	
Curl resultant to heat	ISO 19322 - PROCEDURE A	≤ 1 mm	
Reaction to fire	EN 13501-1	Cfl-s1	
Residual indentation	EN ISO 24343-1	≤ 0.1 mm	
Furniture leg	ISO 16581 - EN 424	No damage	
Castor chair	ISO 4918 - EN 425	No damage	
Impact sound reduction	EN ISO 717-2	ΔLw = 2 dB	
Reduction of in-room impact noise	NF S31-074	Class C (L _{ne,w} < 85 dB)	
Thermal resistance	EN ISO 10456	0.02 m ² K/W	
Light fastness	EN ISO 105-B02 (method 3a)	≥ 6	
Chemical resistance	EN ISO 26987	Very Good	
Slip resistance	DIN 51130 EN 13893	R9/R10 depending on embossing μ ≥ 0,30	
Electrical properties	EN 1815 EN 1081	< 2kV on concrete > 10 ⁹ Ω	
Peeling resistance	EN ISO 24345	≥ 50N / 50mm	
Underfloor heating		Suitable - max. 27 °C (See installation notice)	
Environmental performances			
TVOC 28 days AgBB test	ISO 16000-9	≤ 10 μg/m ³	

The above information is subject to modification for the benefit of further improvement. (12/18).

According to the European Regulation N° 305/2011 for CE Marking, the Declarations of Performance are available on our website www.tarkett.com

Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for these instructions.

CUSTOMS TARIFF : 4820 5000 00



*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).

