

iD SUPERNATURE

TECHNICAL DATA

Certification & classification	Standards	iD SUPERNATURE 55	iD SUPERNATURE 70
Type of floor covering	EN ISO 10582	Heterogeneous Compact Resilient Floorcovering	Heterogeneous Compact Resilient Floorcovering
Classification	EN ISO 10874	Domestic: 23 Commercial: 33 Industrial: 42	Domestic: 23 Commercial: 34 Industrial: 43
Technical characteristics			
Total thickness	EN ISO 24346	2,5 mm	2,5 mm
Wear layer thickness	EN ISO 24340	0,55 mm	0,7 mm
Total weight	EN ISO 23997	3850 g/m ²	3950 g/m ²
Wear layer binder content	EN ISO 10582	Type I	Type I
Dimensions	EN ISO 24342	Standard formats Planks 10 x 50 cm 75 planks per box = 3.75 m ² 16,66 x 100 cm 22 planks per box = 3.67 m ² 12,5 x 122 cm 24 planks per box = 3.66 m ² 20 x 122 cm 15 planks per box = 3.66 m ² Tiles 25 x 50 cm (for stone designs only) 30 tiles per box = 3.75 m ² 50 x 50 cm (for stone designs only) 15 tiles per box = 3.75 m ² 50 x 100 cm* (for stone designs only) 7 tiles per box = 3.5 m ² 100 x 100 cm* (for stone designs only) 70 tiles per pallet 100 x 150 cm* (for stone designs only) 47 tiles per pallet Special formats Small Hexagon 20 x 23.094 cm 60 planks per box = 2.08 m ² Large Hexagon 33.33 x 38.486 cm 20 planks per box = 1.92 m ² Left & Right Herringbone 8.33 x 38.486 cm 80 planks per box = 2.56 m ²	
Surface treatment (PUR)		Yes - TopCleanXP™	Yes - TopCleanXP™
Beveled edges		Yes (16,66x100cm 25x50cm 50x50cm 50x100cm 100x100cm 12,5x122cm 20x122cm 150x100cm)	Yes (16,66x100cm 25x50cm 50x50cm 50x100cm 100x100cm 12,5x122cm 20x122cm 150x100cm)
Technical performances			
Dimensional stability	EN ISO 23999	≤ 0,10 %	≤ 0,10 %
Curl resultant to heat	EN ISO 23999	≤ 2 mm	≤ 2 mm
Reaction to fire	EN 13501-1	B _{fl} -s1 glued over concrete substrate B _{fl} -s1 glued over wood substrate	B _{fl} -s1 glued over concrete substrate B _{fl} -s1 glued over wood substrate
Residual indentation	EN ISO 24343-1	≤ 0,05 mm	≤ 0,05 mm
Furniture leg	EN 424	No damage	No damage
Castor chair	ISO 4918 - EN 425	No damage	No damage
Impact sound reduction	EN ISO 717-2	ΔL _w = 2 dB	ΔL _w = 2 dB
Reduction of in-room impact noise	EN ISO 31-074	Class C (L _{n,e,w} < 85 dB)	Class C (L _{n,e,w} < 85 dB)
Thermal resistance	EN ISO 10456	0,02 m ² K/W	0,02 m ² K/W
Light fastness	EN ISO 105-B02 (method 3a)	≥ 6	≥ 6
Chemical resistance	EN ISO 26987	Very good	Very good
Slip resistance	DIN 51130 EN 13893	R9 μ ≥ 0,30	R9 μ ≥ 0,30
Electrical properties	EN 1815 EN 1081	<2 kV on concrete > 10 ⁹ Ohm	<2 kV on concrete > 10 ⁹ Ohm
Peeling resistance	EN ISO 24345	≥ 50N / 50mm	≥ 50N / 50mm
Underfloor heating		Suitable - max. 27 °C	Suitable - max. 27 °C
Environmental TAG			
VOC emission	ISO 16000-9	≤ 10μg/m ³	≤ 10μg/m ³
Recycled content	-	32%	32%
Recyclable	-	100%	100%
Plasticizer	-	Phtalate-free	Phtalate-free
CE Marking			
DoP number	-	0004-0038-DOP-2016-09	0004-0041-DOP-2016-09

*Not available with iD Tattoo

CUSTOMS TARIFF : 4820 5000 00

The above information is subject to modification for the benefit of further improvement. (10/18).

Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for these instructions.



*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).

