

TECHNICAL SPECIFICATIONS

Bevel	Painted	Class of use (ISO 10582)	Class 34
Lock	N/A	Installation	Glue down
Layer	Thickness (mm)	Type	
Top Layer	0.7	Ceramic bead enhanced UV coating	
Core	2.3	Waterproof thermoplastic composite	
Total	3.0		

CERTIFICATIONS & CHEMICAL PROPERTIES




Norm	Item	Test method	Requirement	Result
EN 14041	Emissions	EN 717-1	≤ 0.124 mg/m3	E1
Decret No2011-321	Emissions	ISO 16000	TVOC<1000µg/m3	VOC A+
GreenGuard Gold	Emissions	Spectrometry, chromatography	TVOC≤220µg	Certified, requests private label application
Prop 65	Orthophthalates	Spectrometry	ND	Compliant
CPSIA	Lead	CPSC-CH-E-1002-08	≤ 90ppm	Compliant
EU REACH Regulation	PAHs	Spectrometry, chromatography	<1mg/kg	Compliant
	SVHC	Spectrometry, chromatography	≤ 0.1% (w/w)	Compliant
EN 14041	CE Certification	Multiple	Multiple	Compliant

PHYSICAL PROPERTIES

Norm	Item	Test Method	Requirement	Result
ISO 10582	Dimensional stability	ISO 23999	≤ 0.15%	Compliant
	Curling	ISO 23999	≤ 1mm	Compliant
	Length tolerance	ISO 24342	≤ 0.15% of nominal length up to 0.5 mm max.	Compliant
	Width tolerance	ISO 24342	≤ 0.10% of nominal width up to 0.5 mm max.	Compliant
	Thickness tolerance	ISO 24346	+0.13mm -0.10mm	Compliant
	Squareness	ISO 24342	≤0.25mm/≤400mm ≤0.35mm/≥400mm	Compliant
	Flatness	ISO 10582 Appendix B	Length: ≤ 0.50% (concave) ≤ 1.0% (convex) Width: ≤ 0.10%(concave) ≤ 0.15% (convex)	Compliant
	Openings between tiles/planks	ISO 10582 Appendix C	0.20mm	Compliant
	Height difference between tiles/planks	ISO 10582 Appendix C	0.15mm	Compliant
	Residual indentation	ISO 24343-1	≤0.1mm	Compliant
	Castor chair	ISO 4918	Slight change only	Compliant
	Resistance to heat	ISO 105-802:2014	≥ Grade 6	Compliant
		ASTM F1515	ΔE ≤8	Compliant
	ISO 16511	Wear resistance	EN 13329	≥4000R
Impact resistance		EN 13329	≥1600mm	Compliant
Micro scratch		EN 16094	≤ MSR-A3	Compliant
Resistance to staining		EN 438-2	Group 1 and 2; grade 5, group3: grade 4	Compliant
ASTM F1700	Residual indentation	ASTM F1914	Ave ≤8% (140lbs/63.5kg);max ≤10%	Compliant
	Resistance to chemicals	ASTM F925	Slight change only	Compliant
EN 14041	Resistance to light	ASTM F1514	ΔE ≤8	Compliant
	Thermal resistance (R)	EN 12667/ASTM C518	NA	Suitable for underfloor heating systems
	Slipperiness	EN 13893	≥ 0.3	Compliant
Others	Reaction to fire	EN 13051-1	NA	Class Bfl -S1
	Density	ISO 23996	NA	Around 1950 kg/m3
	Resistance to light	ISO 105-802:1994,	≥ Grade 6	Compliant
	Slipperiness	DIN 51130	≥R9	R9
	Fire resistance (CHF)	ASTM E648/NFPA 253	≥0.45	Class 1

LEED SCORECARD

LEED was developed to address all buildings everywhere, regardless of where they are in their life cycle. From hospitals to data centers, from historical buildings to those still in the design phase, there is a LEED certification program for every building. Our products will contribute value to a building's LEED v4 Scorecard in the following LEED certification program categories recognized by the USGBC as per following

LEED Programme Certification	Category	Credit Title	LEED Points Attainable	Credit Description	How our product contributes to obtaining LEED points
 Building Design and Construction	Indoor Environmental Quality	Credit 1: Enhanced Indoor Air Quality Strategies – Option 2 Additional Enhanced IAQ Strategie - option D	1 point ID&C, 2 points Retail CI	To reduce concentrations of chemical that can damage air quality, human health, productivity, and the environment.	1. Formaldehyde emission are less than 0.05mg/m3, TVOCs are less than 0.5mg/m3. 2. The product is GreenGuard Gold certified.
		Credit 2: Low-Emitting Materials – Option1 Flooring	1 point		1. VOC emission are less than 0.5mg/m3. 2. The products is GreenGuard Gold certified.
		Credit 4: Indoor Air Quality Assessment - Option 2 Air Testing	2 points	To establish better quality indoor air in the building	1. Formaldehyde emission are less than 0.05mg/m3, TVOCs are less than 0.5mg/m3. 2. The product is GreenGuard Gold certified.
		Credit 4: Material ingredient– Option 2 Credit 6 – PBT source reduction: lead, cadmium and copper	1 point 1 point	Minimize the use and generation of harmful substances To reduce the release of persistent, bioaccumulative, and toxic chemicals	The product is 100% REACH compliant The product is free of lead, cadmium and copper
 Building Operations and Maintenance	Material & Resource	Credit 3: Purchasing - Facility maintenance and renovation	1 point	To reduce the environmental harm from materials used in building renovations	1. The product is 100% REACH compliant 2. Formaldehyde emission are less than 0.05mg/m3, TVOCs are less than 0.5mg/m3. 3. Test report according to ISO 16000 is available on request. 3. The product is GreenGuard Gold certified.
 Homes	Indoor Environmental Quality	Credit 2: Contaminant Control – Option 4 Air Testing	1 point	Demonstrate that contaminants do not exceed concentration levels listed	The products is GreenGuard Gold certified.
		Credit 7: Low-Emitting Materials	0.5 point	To reduce occupants' exposure to airborne chemical contaminants	The product is GreenGuard Gold certified and meet the requirements of CA Section 01350. The product is made with ULEF or non-added formaldehyde material
	Material & Resource	Prerequisite – Durability management	0 point (Prerequisite)	To promote durability and performance of the building	The product is water resistant



Indoor Environmental Quality

Credit 1: Enhanced Indoor Air Quality Strategies – Option 2 Additional Enhanced IAQ Strategies - option D 1 point ID&C, 2 points Retail CI

Credit 2: Low-Emitting Materials – Option 1 Flooring 1 point

Credit 4: Indoor Air Quality Assessment - Option 2 Air Testing 2 points

To reduce concentrations of chemical contaminants that can damage air quality, human health, productivity, and the environment.

To establish better quality indoor air in the building

1. Formaldehyde emission are less than 0.05mg/m3, TVOCs are less than 0.5mg/m3.
2. The product is GreenGuard Gold certified.

1. VOC emission are less than 0.5mg/m3.
2. The products is GreenGuard Gold certified.

1. Formaldehyde emission are less than 0.05mg/m3, TVOCs are less than 0.5mg/m3.
2. The product is GreenGuard Gold certified.

Material & Resource

Credit 4: Material ingredient– Option 2 1 point

Minimize the use and generation of harmful substances

The product is 100% REACH compliant

WELL SCORECARD

The WELL Building Standard is founded on the understanding that facets of our environment interact with personal, genetic and behavioral factors to shape our overall health and well-being. By compiling leading practices in building design and management and referencing existing standards and best practice guidelines set by governmental and professional organizations, WELL works to harmonize and clarify existing thresholds and requirements.

Facet	Feature	Part	Requirements	Concept score	How our product contribute to obtain WELL level certification
AIR	01. Air quality standards	1. Standards For Volatile Substances	The following conditions are met: a. Formaldehyde levels less than 27ppb (0.027ppm) b. Total volatile organic compounds less than 500ug/m3 (0.5mg/m3)	PRECONDITION	a. Formaldehyde emission are less than 0.05mg/m3. b. The total volatile organic compounds are less than 0.5mg/m3.
		04. VOC Reduction	1. Interior Paints and Coatings	The VOC limits of newly applied paints and coating meet one of the following requirements: a. 100% of installed products meet California Air Resources Board (CARB) 2007, Suggested Control Measure (SCM) for Architectural Coatings, or South Coast Air Quality Management District (SCAQMD) Rule 1113, effective June 3, 2011 for VOC content. b. At minimum 90%, by volume, meet the California Department of Public Health (CDPH) Standard Method v1.1-2010 for VOC emissions	PRECONDITION
		3. Flooring	The VOC emissions of all newly installed flooring must meet all limits set by the following, as applicable: a. California Department of Public Health (CDPH) Standard Method v1.1-2010.	PRECONDITION	Conforms to the CDPH/EHLB Standard Method v1.1-2010 (California Section 01350), effective January 1, 2012, for the school classroom and private office parameters when modeled as Flooring. The product is GreenGuard Gold certified
	11. Fundamental Material Safety	1. Asbestos and Lead Restriction	All newly-installed building materials meet the following materials composition requirements: a. No asbestos. b. Not more than 100 ppm (by weight) added lead.	PRECONDITION	a. No asbestos b. The product contain less than 100 ppm.
		2. Lead Abatement	For repair, renovation or painting on buildings constructed prior to any applicable laws banning or restricting lead paint, lead evaluation and abatement.	PRECONDITION	The product contain less than 90 ppm.
		3. Asbestos Abatement	To reduce hazards in buildings constructed prior to any applicable laws banning or restricting asbestos, the following testing, evaluation and abatement.	PRECONDITION	The product contain less than 90 ppm.
	25. Toxic Material Reduction	2. Flame Retardant Limitation	Halogenated flame retardants are limited in the following components to 0.01% (100 ppm) to the extent allowable by local code: a. Window and waterproofing membranes, door and window frames and siding. b. Flooring, ceiling tiles and wall coverings. c. Piping and electrical cables, conduits and junction boxes. d. Sound and thermal insulation. e. Upholstered furniture and furnishings, textiles and fabrics.	OPTIMIZATION	The product don't contain halogenated flame retardants
		3. Phthalate (Plasticizers) Limitation	DEHP, DBP, BBP, DINP, DIDP or DNOP (often found in polyvinyl chloride [PVC]) are limited in the following components to 0.01% (100 ppm): a. Flooring, including resilient and hard surface flooring and carpet. b. Wall coverings, window blinds and shades, shower curtains, furniture and upholstery. c. Plumbing pipes and moisture barriers.	OPTIMIZATION	In accordance with US Consumer Product Safety Improvement Act 2008 (CPSIA) (H.R.4040) Title I, Section 108 & California Proposition 65 & Annex XV II item 51&52 of the REACH Regulation (EC) No. 1907/2006 and amendment No. 552/2009, the product contains less than 100ppm.
		5. Urea-Formaldehyde Restriction	Urea-formaldehyde presence is limited in the following components to 100 ppm: a. Furniture or any composite wood products. b. Laminating adhesives and resins. c. Thermal insulation.	OPTIMIZATION	The product contains urea-formaldehyde less than 100ppm.

END OF DOCUMENT